



Bill of Material		
Part number	Part Name	QUANTITY
1	INNER FRAME	1
2	OUTER FRAME	1
3	PUSH LATCH	2
4	SAFETY LATCH	1
5	FREE PIVOTING HINGE	2

PRODUCT	DOOR SIZE	CUTOUT SIZE
RFAP2525PCMR	250	256
RFAP3030PCMR	300	306
RFAP4545PCMR	450	456
RFAP6060PCMR	600	606

MATERIAL DATASHHET

SR.NO	COMPONENTS	MATERIAL/GRADE
1.	Metal frames	Aluminium Alloy 6063, Temper 6
2.	Corner components	1mm GI (galvanized coating 90microns)
3.	Inlay	Moistbloc Plasterboard (Gypsum)
4.	Screws	25 X 6mm Black Phosphate steel.
5.	Safety latch wirerope	1.5mm Steel wirerope (PVC coated)
6.	Powder coating	GStyleE08T RAL 9016 SMO

Characteristics

Non-fire rated standard aluminium access panel frames are electrostatic powder coated white, with MR Grade Gypsum board facing, Providing easy access to gypsum ceilings. Each panel features a push-catch closing mechanism, with door retaining safety cable and hook.

Applications

Suitable for applications where access to services above gypsum ceiling are specified.

Features

- **Frame** - Recessed Aluminium Extrusions with finishing edges.
- **Door Inlays** - MR Gypsum board(Standard), Regular Gypsum board(Optional), Wpc board (Optional), Hilux board (Optional).
- **Locking Mechanism** - Concealed push latch (Standard), Allen Key lock (Optional), Keyed lock (Optional)
- **Hinge** - Free Pivoting Hinge
- **Sealing** - Weather Strip (Grey, Air & Smoke tight)
- **Safety cables** - Snap hook with eyelid and strong wirerope.

